

## TURBOVAC TABLE TOPS:

BEST CHOICE FOR RESTAURANTS, HOSPITALITY INDUSTRY, FOOD VENDORS AND CATERERS.

Our 4 table top machines have all the quality engineering and build of our industrial vacuum machines.



“PLUG & PLAY”

TABLE TOP RANGE  
S20, S30, S40



Liquid insert plate



CABINET FOR  
S20, S30 & S40

### SPECIFICATIONS TABLE TOPS

Transparent cover & stainless steel chamber

	SEAL LENGTH	MAX. PRODUCT HEIGHT	USEFUL CHAMBER SIZE (wxdxh)	OUTSIDE DIMENSION (wxdxh)	STANDARD VOLTAGE*	POWER CONSUMPTION	WEIGHT
TABLE TOP <b>S20</b>	270	100	270 x 310 x 100/140**	365 x 500 x 300/340**	230-1-50 Hz	0,4/0,5 kW	25 kg
TABLE TOP <b>S30</b>	320	160	320 x 330 x 160	430 x 550 x 410	230-1-50 Hz	0,5/0,7 kW	50 kg
TABLE TOP <b>S40</b>	420	180	max. 420 x 370 x 180	530 x 590 x 460	230-1-50 Hz	0,7/1,3 kW	60 kg
TABLE TOP <b>S50</b>	320	95	800 x 320 x 95	985 x 515 x 430	230-1-50 Hz	1,3 kW	115 kg

Dimensions in mm \*Machines can be supplied with all world wide voltages applicable

### OPTIONS TABLE TOPS

	DIGITAL TIME CONTROL	SENSOR CONTROL	SEAL	SEAL CONFIGURATION	GAS	PUMP CAPACITY M <sup>3</sup>	CYCLE TIME
TABLE TOP <b>S20**</b>	1 program	x	Single	L	x	4 or 8 m <sup>3</sup>	20-40 sec
TABLE TOP <b>S30</b>	1 or 10 programs	sensor/H <sub>2</sub> O	Double/CC***	L	gas	8 or 16 m <sup>3</sup>	20-30 sec
TABLE TOP <b>S40</b>	1 or 10 programs	sensor/H <sub>2</sub> O	Double/CC***	L L&L	gas	16 or 21 m <sup>3</sup>	20-30 sec
TABLE TOP <b>S50</b>	1 or 10 programs	sensor/H <sub>2</sub> O	Double/CC***	S&S	gas	21 m <sup>3</sup>	20-30 sec

\*\*Model S20 standard coverheight 100 mm, optional cover 140 mm height

\*\*\*CC = Clean Cut, (Clean Cut)

### SPECIFICATIONS CABINET

CABINET	DIMENSIONS (wxdxh)	FOR TABLE TOP
<b>PLUS-1</b>	450 x 550 x 620	S20 & S30
<b>PLUS-2</b>	540 x 590 x 580	S40

### SEAL CONFIGURATIONS TABLE TOPS

